



CMX8204 4Ch

1 SATA(6TB) 4ch Analog HD DVR



CMX8208 8Ch

1 SATA(6TB) 8ch Analog HD DVR



CMX8216 16Ch

2 SATA(12TB) 16ch Analog HD DVR

HIP

Best Security

CCTV SYSTEM



HIP Camera HIP CCTV application



	Model	CMX8204	CMX8208	CMX8216
System	processor	Hi3520D	Hi3521A	Hi3531A
Video	Codec	H.264	H.264	H.264
	Encode	4*1080P@15fps	8*1080P@12fps,8*1080N	16*1080P@12fps,8*1080P,16*1080N
	Decode	4*1080P@15fps	4*1080P@12fps,8*1080N	16*1080P@12fps,8*1080P,16*1080N
	Multi-mode	Analog: 4*1080P@15fps Hybird: 4*1080N(analog)+4*960P(ip) IP: 4*5M; 9*1080P; 16*1080P; 16*960P	Analog: 8*1080P@12fps,8*1080N Hybird: 4*1080P(analog)+4*1080P(ip) IP: 4*5M; 4*3M; 8*1080P+8*960P; 16*960P	Analog: 16*1080P@12fps; 8*1080P; 16*1080N Hybird: 8*1080P(analog)+8*1080P(ip) IP: 4*5M; 8*3M; 8*1080P+8*960P
Audio	Playback Compression	4ch G.711a	8ch G.711a	16ch G.711a
Management	Intercom	Support	Support	Support
	Record mode	Manual>Alarm>Motion detection>Timing	Manual>Alarm>Motion detection>Timing	Manual>Alarm>Motion detection>Timing
	Inquire mode	Inquire by Time/Calendar/Event/Channel	Inquire by Time/Calendar/Event/Channel	Inquire by Time/Calendar/Event/Channel
	Storage mode	HDD Storage, Network Storage	HDD Storage, Network Storage	HDD Storage, Network Storage
Interface	Backup	Network, USB, SATA	Network, USB, SATA	Network, USB, SATA
	Video input	4*BNC(Support Coaxitron)	8*BNC(Support Coaxitron)	16*BNC(Support Coaxitron)
	HDMI output	1*HDMI (MAX:1080P)	1*HDMI (MAX:1080P)	1*HDMI (MAX:4K)
	VGA output	1*VGA (MAX:1080P)	1*VGA (MAX:1080P)	1*VGA (MAX:1080P)
	Audio I/O	4/1	4/1	6/1
	Alarm I/O	0/0	0/0	4/1
	Ethernet port	1*10/100Mbps Ethernet port, RJ45 port	1*10/100Mbps Ethernet port, RJ45 port	1*10/100Mbps Ethernet port, RJ45 port
	PTZ control	1*RS485, Support for multiple PTZ protocol	1*RS485, Support for multiple PTZ protocol	1*RS485, Support for multiple PTZ protocol
	USB Port	2*USB2.0 ports	2*USB2.0 ports	2*USB2.0 ports
	General	HDD	1*SATA interface (Up to 6TB)	1*SATA interface (Up to 6TB)
Temperature		0°C - + 55°C	0°C - + 55°C	0°C - + 55°C
Humidity		10% -90% RH	10% -90% RH	10% -90% RH
Power supply		12V/2A	12V/2A	12V/4A
Consumption		<10W(Without HDD)	<10W(Without HDD)	<10W(Without HDD)
Weight		Around 1KG	Around 1KG	Around 1.8KG
Dimension		255(L)* 236mm(W)* 44mm(H)	255(L)* 236mm(W)* 44mm(H)	310mm(L)* 298mm(W)* 60mm(H)

DVR 5in1 AHD

Digital Video Recorder

TVI AHD CVBS CVI IP

ขอสงวนสิทธิ์ในการเปลี่ยนแปลงรายละเอียดทั้งหมดโดยไม่ต้องแจ้งให้ทราบล่วงหน้าโดย บริษัท เอช ไอ พี ไทเทค จำกัด.

